

Paint Thinner

SECTION 1. IDENTIFICATION

Product Identifier	Paint Thinner
Other Means of Identification	13-221, 13-224, 13-228, 13-321, 13-324, 13-324HD,, 13-324TAR, 13-325, 13-328, 13-341, 13-344, 13-371, 13-374, 13-374HD, 13-375, 14-534, 14-534IMDG, 14-535, 14-538, 14-538UN, 14-573, 23-229, 23-329, 23-329UN, 23-379, 23-379-M, 24-539, 24-539-1000, 33-319UFA, 33-321ACE, 33-321D, 33-321FSEXP, 33-321H, 33-321PAEXP, 33-321PLYEXP, 33-321PP, 33-321RONA, 33-324ACE, 33-324CL, 33-324D, 33-324FSEXP-PRO, 33-324H, 33-324PAEXP-PRO, 33-324PLYX-PRO, 33-324PP, 33-324RONA, 33-324TH, 33-325FSEXP-PRO, 33-325PAEXP-PRO, 33-325PP, 33-326PLYX-PRO, 33-328FSEXP-PRO, 33-328PAEXP-PRO, 33-328PLYX-PRO, 33-328UNI, 33-371H, 33-374H, 33-375H, 34-531C, 34-531FSEXP, 34-531H, 34-531PAEXP, 34-531WDS, 34-534C, 34-534FSEXP-PRO, 34-534H, 34-534PAEXP-PRO, 34-534PLYX-PRO, 34-534RONA, 34-534WDS, 34-535C, 34-535FSEXP-PRO, 34-535H, 34-535PAEXP-PRO, 34-535PLYX-PRO, 34-535RONA, 34-535STE, 34-535WDS, 34-538FSEXP-PRO, 34-538H, 34-538PAEXP, 34-538PAEXP-PRO, 34-538PLYX-PRO, 34-539UFA, 34-573C-CL, 34-573H, 34-574HH, 83-228, 83-229, 83-321, 83-324, 83-326, 83-328, 83-341, 83-344, 84-534, 84-535, 84-538, 84-539, 14-802, 14-804, 34-802SI, 84-802, 84-802ISR, 84-804ISR, 34-803WDS, 34-802WDS, 34-804WDS, 34-802SIEXP, 13-348LAU, 14-402, 14-535UFA, 14-802EXP, 34-802SIB40, 24-539LAU, 24-539U/N, 33-228FN, 33-324ZIEXP, 34-573WDS-CL, 83-229-40, 83-329SHER, 83-329DU, 84-538-40, 84-539-40
Other Identification	Solvent, Varsol, Citronella, Charcoal Lighter Fluid, Kerosene, Lamp Oil, Mineral Spirits
Recommended Use	Please refer to Product label.
Restrictions on Use	None known.
Manufacturer/Supplier Identifier	Recochem Inc., 850 Montee de Liesse, Montreal, QC, H4T 1P4, Compliance and Regulatory Department, 905-878-5544, www.recochem.com
Emergency Phone No.	CANUTEC, 613-996-6666, 24 Hours
SDS No.	1777

SECTION 2. HAZARD IDENTIFICATION

Classification

Flammable liquid - Category 3; Skin irritation - Category 2; Eye irritation - Category 2A; Germ cell mutagenicity - Category 1B; Carcinogenicity - Category 1B; Specific target organ toxicity (single exposure) - Category 3; Specific target organ toxicity (repeated exposure) - Category 2; Aspiration hazard - Category 1; Aquatic hazard (Chronic) - Category 2

Label Elements



Signal Word:
Danger

Product Identifier: Paint Thinner - Ver. 1
Date of Preparation: May 08, 2017
Date of Last Revision:

SDS No.: 1777

Page 01 of 10

Hazard Statement(s):

- H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 + H320 Causes skin and eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H340 May cause genetic defects.
H350 May cause cancer.
H373 May cause damage to organs (nervous system) through prolonged or repeated exposure if inhaled.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statement(s):

Prevention:

- P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical, ventilating, and lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe fume, mist, vapours, spray.
P264 Wash hands and skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves, eye protection, face protection.

Response:

- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor.
P331 Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P312 Call a POISON CENTRE or doctor if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical advice or attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 Call a POISON CENTRE or doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTRE or doctor if you feel unwell.
P337 + P313 If eye irritation persists: Get medical advice or attention.
P370 + P378 In case of fire: Use appropriate foam, carbon dioxide, dry chemical powder, water spray or fog to extinguish.
P391 Collect spillage.

Storage:

Store in a well ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.

Note:

1-5
. % of the mixture consists of ingredient(s) of unknown acute toxicity.

Product Identifier: Paint Thinner - Ver. 1

SDS No.: 1777

Date of Preparation: May 08, 2017

Date of Last Revision:

Page 02 of 10

Other Hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture:

Chemical Name	CAS No.	%	Other Identifiers	Other Names
Stoddard solvent	8052-41-3	80-100		
n-Nonane	111-84-2	1-5	Constituent Contained in Complex Mixture	
1,2,4-Trimethylbenzene	95-63-6	1-5	Constituent Contained in Complex Mixture	
Naphthalene	91-20-3	0.1-1	Constituent Contained in Complex Mixture	
Xylene (mixed isomers)	1330-20-7	0.1-1	Constituent Contained in Complex Mixture	
Ethylbenzene	100-41-4	0.1-1	Constituent Contained in Complex Mixture	

Notes

Use of Generic SDS:

If the concentration or actual concentration range of an ingredient of a particular hazardous product in the series is different from the concentration or actual concentration range disclosed for the rest of the series, either the concentration or the actual concentration range must be indicated beside that ingredient under item 3 (Composition/Information on ingredients) of the SDS. Furthermore, if any other specific information element(s) (such as flash point, numerical measure of toxicity, etc.) for a particular hazardous product in the series differs from that of the other products in the series (without affecting the classification), the information element relevant to that hazardous product must be disclosed on the SDS with an indication to which hazardous product each relates.

Source: Health Canada - Technical Guidance on the Requirements of the Hazardous Products Act and the Hazardous Products Regulations WHMIS 2015 Supplier Requirements - pg 117

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

Take precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). Remove source of exposure or move to fresh air. Keep at rest in a position comfortable for breathing. Call a Poison Centre or doctor if you feel unwell.

Skin Contact

Avoid direct contact. Wear chemical protective clothing if necessary. Take off contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 5 minutes. Call a Poison Centre or doctor if you feel unwell. If skin irritation occurs, get medical advice or attention. Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely.

Eye Contact

Avoid direct contact. Wear chemical protective gloves if necessary. Quickly and gently blot or brush chemical off the face. Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. Remove contact lenses, if present and easy to do. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists, get medical advice or attention.

Product Identifier: Paint Thinner - Ver. 1

SDS No.: 1777

Date of Preparation: May 08, 2017

Date of Last Revision:

Page 03 of 10

Ingestion

Do not induce vomiting. Rinse mouth with water. Never give anything by mouth if person is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting. If vomiting occurs naturally, lie on your side in the recovery position. Rinse mouth with water again. If breathing has stopped, trained personnel should immediately begin rescue breathing. Immediately call a Poison Centre or doctor.

Most Important Symptoms and Effects, Acute and Delayed

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Immediate Medical Attention and Special Treatment

Target Organs

Eyes, skin, respiratory system.

Special Instructions

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Medical Conditions Aggravated by Exposure

Dermatitis.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, dry chemical powder, appropriate foam, water spray or fog.

Unsuitable Extinguishing Media

None known.

Specific Hazards Arising from the Product

Flammable liquid and vapour. Can ignite at room temperature. Releases vapour that can form explosive mixture with air. Can be ignited by static discharge. Can accumulate static charge by flow, splashing or agitation. Liquid can float on water and may travel to distant locations and/or spread fire. See Section 9 (Physical and Chemical Properties) for flash point and explosive limits. Closed containers may rupture violently when heated releasing contents.

In a fire, the following hazardous materials may be generated: irritating chemicals; toxic chemicals; very toxic carbon monoxide, carbon dioxide.

Special Protective Equipment and Precautions for Fire-fighters

Review Section 6 (Accidental Release Measures) for important information on responding to leaks/spills. See Skin Protection in Section 8 (Exposure Controls/Personal Protection) for advice on suitable chemical protective materials.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

No special precautions are necessary. Evacuate downwind locations. Use the personal protective equipment recommended in Section 8 of this safety data sheet. Increase ventilation to area or move leaking container to a well-ventilated and secure area. Eliminate all ignition sources. Use grounded, explosion-proof equipment.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway.

Methods and Materials for Containment and Cleaning Up

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Product Identifier: Paint Thinner - Ver. 1

SDS No.: 1777

Date of Preparation: May 08, 2017

Date of Last Revision:

Page 04 of 10

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for Safe Storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Stoddard solvent	100 ppm	Not established	100 ppm	Not established		
Naphthalene	10 ppm A3	Not established	10 ppm	15 ppm		
n-Nonane	200 ppm	Not established	200 ppm	Not established		
1,2,4-Trimethylbenzene	25 ppm	Not established	25 ppm	Not established		
Xylene (mixed isomers)	100 ppm	150 ppm	100 ppm	150 ppm		
Ethylbenzene	100 ppm	125 ppm	100 ppm	125 ppm		

Appropriate Engineering Controls

General ventilation is usually adequate. For large scale use of this product: use local exhaust ventilation, if general ventilation is not adequate to control amount in the air. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored. Control static electricity discharges which includes bonding of equipment to ground. Use only non-combustible, compatible materials for walls, floors, ventilation system, air cleaning devices, pallets, shelving. Provide eyewash and safety shower if contact or splash hazard exists.

Individual Protection Measures

Eye/Face Protection

Wear chemical safety goggles.

Skin Protection

Wear chemical protective clothing e.g. gloves, aprons, boots.

Respiratory Protection

Not normally required if product is used as directed. For non-routine or emergency situations: wear a NIOSH approved air-purifying respirator with an appropriate cartridge.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Available in these colours: Clear, Yellow, Gold, Red, Blue, Green, Amber, Pink, Orange, Purple, White, Brown.
Odour	Hydrocarbon
Odour Threshold	Not available
pH	Not available
Melting Point/Freezing Point	-76 °C (-105 °F) (melting); -76 °C (-105 °F) (freezing)
Initial Boiling Point/Range	159 - 195 °C (318 - 383 °F)
Flash Point	43 °C (109 °F) (closed cup)
Evaporation Rate	0.1 (n-butyl acetate = 1)
Flammability (solid, gas)	Not applicable
Upper/Lower Flammability or Explosive Limit	5.6% (upper); 0.8% (lower)
Vapour Pressure	3.98 - 4.50 mm Hg (0.53 - 0.60 kPa) at 25 °C
Vapour Density (air = 1)	5
Relative Density (water = 1)	0.788 at 15 °C
Solubility	Insoluble in water; Not available (in other liquids)
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	260 °C (500 °F)
Decomposition Temperature	Not available
Viscosity	1.21 centistokes at 25 °C (kinematic); Not available (dynamic)
Other Information	
Physical State	Liquid
Molecular Weight	Not applicable
Other Physical Property 1	Additional Appearance: Clear Yellow Liquid

SECTION 10. STABILITY AND REACTIVITY

Reactivity

None known.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

None known.

Conditions to Avoid

Open flames, sparks, static discharge, heat and other ignition sources. Temperatures above 43.0 °C (109.4 °F)

Incompatible Materials

Reacts explosively with: strong oxidizing agents (e.g. perchloric acid).

Not corrosive to metals.

Hazardous Decomposition Products

None known.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Product Identifier: Paint Thinner - Ver. 1

Date of Preparation: May 08, 2017

Date of Last Revision:

SDS No.: 1777

Page 06 of 10

Skin contact; eye contact; inhalation.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Stoddard solvent	> 5500 mg/m3 (rat) (4-hour exposure)	5000 mg/kg (rat)	> 3000 mg/kg (rabbit)
Naphthalene	739.2 mg/m3 (rat) (4-hour exposure)	316 mg/kg (mouse)	> 20000 mg/kg (rabbit)
n-Nonane	3200 ppm (rat) (4-hour exposure)	15 g/kg (rat)	Not available
1,2,4-Trimethylbenzene	18000 mg/m3 (rat)	5000 mg/kg (rat)	Not available
Xylene (mixed isomers)	6350 mg/m3 (male rat) (4-hour exposure)	3523 mg/kg (rat)	> 1700 mg/kg (rabbit)
Ethylbenzene	4400 ppm (rat) (4-hour exposure)	3500 mg/kg (rat)	15380 mg/kg (rabbit)

LC50: Not applicable.

LD50 (oral): Not applicable.

LD50 (dermal): Not applicable.

Skin Corrosion/Irritation

Animal tests show moderate or severe irritation.

Serious Eye Damage/Irritation

Human experience shows mild irritation. The vapour also irritates the eyes.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause depression of the central nervous system. Symptoms may include headache, nausea, dizziness, drowsiness and confusion. Nose and throat irritation. At high concentrations.

Skin Absorption

No information was located.

Ingestion

Not harmful based on animal tests.

Aspiration Hazard

Can cause lung damage if aspirated based on human experience. Death can result.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

Causes damage to organs based on studies in people. If inhaled: effects similar to STOT (Specific Target Organ Toxicity) - Single Exposure, as described above, effects on the central nervous system, "organic solvent syndrome". Causes Following skin contact: dermatitis. Symptoms may include dry, red, cracked skin (dermatitis). effects similar to STOT (Specific Target Organ Toxicity) - Single Exposure, as described above. May cause damage to organs based on limited evidence. If inhaled and/or following skin contact: at high concentrations harmful effects on the kidneys, harmful effects on the liver. May cause damage to organs based on limited evidence. If inhaled and/or following skin contact: blood tests may show abnormal results.

Respiratory and/or Skin Sensitization

No information was located. No information was located.

Carcinogenicity

Chemical Name	IARC	ACGIH®	NTP	OSHA
Stoddard solvent	Group 3	Not designated	Not Listed	Not Listed
Naphthalene	Group 2B	A3	Reasonably anticipated	Not Listed

n-Nonane	Not Listed	Not designated	Not Listed	Not Listed
1,2,4-Trimethylbenzene	Not Listed	Not designated	Not Listed	Not Listed
Xylene (mixed isomers)	Group 3	A4	Not Listed	Not Listed
Ethylbenzene	Group 2B	A3	Not Listed	Not Listed

Reproductive Toxicity

Development of Offspring

Conclusions cannot be drawn from the limited studies available.

Sexual Function and Fertility

No information was located.

Effects on or via Lactation

No information was located.

Germ Cell Mutagenicity

May be mutagenic based on limited evidence. (Stoddard solvent)

Interactive Effects

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

This section is not required by WHMIS.

This section is not required by OSHA HCS 2012.

Ecotoxicity

Acute Aquatic Toxicity

Chemical Name	LC50 Fish	EC50 Crustacea	ErC50 Aquatic Plants	ErC50 Algae
Stoddard solvent	Not available	Not available		
Naphthalene	0.9-9.8 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour; fresh water)	Not available		
n-Nonane	Not available	Not available		
1,2,4-Trimethylbenzene	7.72 mg/L (Pimephales promelas (fathead minnow); 96-hour)	Not available		
Xylene (mixed isomers)	13.4 mg/L (Oncorhynchus mykiss (rainbow trout); 96-hour; fresh water)	150 mg/L (Daphnia magna (water flea))		
Ethylbenzene	88.00 mg/L (Pimephales promelas (fathead minnow); 96-hour)	2.90 mg/L (Daphnia magna (water flea); 48-hour)		

Chronic Aquatic Toxicity

Chemical Name	NOEC Fish	EC50 Fish	NOEC Crustacea	EC50 Crustacea
Stoddard solvent	Not available		Not available	
Naphthalene	1.8 mg/L (Oncorhynchus		Not available	

Product Identifier: Paint Thinner - Ver. 1

Date of Preparation: May 08, 2017

Date of Last Revision:

SDS No.: 1777

Page 08 of 10

	mykiss (rainbow trout); 3 days; fresh water)			
n-Nonane	Not available		Not available	
1,2,4-Trimethylbenzene	Not available		Not available	
Xylene (mixed isomers)	Not available		Not available	
Ethylbenzene	Not available		Not available	

Persistence and Degradability

No information was located.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

Other Adverse Effects

There is no information available.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	1268	PETROLEUM DISTILLATES, N.O.S.	3	III
US DOT	1268	PETROLEUM DISTILLATES, N.O.S.	3	III

Environmental Hazards Potential Marine Pollutant (1,2,4-Trimethylbenzene)

Special Precautions Please note: In containers of 450 L or less this product is not classified as a Dangerous Good according to TDG Exemption 1.33
In containers of 450L or less, this product meets the requirements of DOT exemption as per 49 CFR, section 173.150 (f).

Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Proof of Dangerous Goods Classification

Date of Classification January 13, 2017
Technical Name PETROLEUM DISTILLATES, N.O.S.
Classification 3 PG III
Classification Method Flashpoint as per Section 9

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Product Identifier: Paint Thinner - Ver. 1
Date of Preparation: May 08, 2017
Date of Last Revision:

SDS No.: 1777

Page 09 of 10

Canada

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All ingredients are listed on the DSL/NDSL.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

All ingredients are listed on the TSCA Inventory.

Additional USA Regulatory Lists

California Proposition 65:

WARNING: Cancer - www.P65Warnings.ca.gov/product.

Custom Regulatory 1

Consumer Product Safety Improvement Act of 2008 General Conformity Certification

The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

SECTION 16. OTHER INFORMATION

SDS Prepared By Compliance and Regulatory Department

Phone No. 905-878-5544

Date of Preparation May 08, 2017

References CHEMINFO database. Canadian Centre for Occupational Health and Safety (CCOHS).

Additional Information We are committed to uphold the Industry Consumer Ingredient Communication Voluntary Initiative.
Please send us your request by visiting our website at www.recochem.com.

Ingredients present (intentionally added ingredients) at a concentration of greater than one percent (1%) shall be listed in descending order of predominance. Ingredients present at a concentration of not more than one percent shall be listed but may be disclosed without respect to order of predominance.

Disclaimer

Notice to reader: To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Product Identifier: Paint Thinner - Ver. 1

SDS No.: 1777

Date of Preparation: May 08, 2017

Date of Last Revision:

Page 10 of 10