

**SE1180
CONSTRUCTION SEALANT****1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Manufacturer Name: Momentive performance material
260 Hudson River Rd
Waterford NY 12188
Revised: 07/06/2012
Prepared by: Product Regulatory Compliance
CHEMTREC 1-800-424-9300
MSDS Contact: 1-888-443-9466
Information: 4information@momentive.com

Chemical Family/Use: Sealant

Formula: Mixture

HMIS

Flammability: 0 Reactivity: 0 Health: 1

NFPA

Flammability: 0 Reactivity: 0 Health: 1

2. HAZARDS IDENTIFICATION**WHMIS Classification**

Toxic Material Causing Other Toxic Effects

Emergency Overview

WARNING! Irritating to eyes, respiratory system and skin.

Form: Solid

Color: White

Odor: Acetic acid.

Potential Health Effects**Ingestion**

May be harmful if swallowed.

Skin

Skin irritation is possible after contact with the uncured product. Uncured product contact will irritate lips, gums and tongue.

Inhalation

Applies in uncured state.

**SE1180
CONSTRUCTION SEALANT****EYES**

Eye irritation on contact with the uncured product.

MEDICAL CONDITIONS AGGRAVATED

None known.

SUBCHRONIC (TARGET ORGAN)

None known.

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

Routes of Exposure

Dermal; Eye

3. COMPOSITION/INFORMATION ON INGREDIENTS**Hazardous Component(s)**

PRODUCT COMPOSITION	CAS-No.	WGT. %
DISTILLATES (PETROLEUM), HYDROTREATED MIDDLE	64742-46-7	10 - 30 %
Methyltriacetoxysilane	4253-34-3	1 - 5 %
Titanium Dioxide	13463-67-7	1 - 5 %

Note(s): See Section 15 for HMIRC information.

4. FIRST AID MEASURES**Ingestion**

If swallowed, do NOT induce vomiting. Give a glass of water.

Skin

To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water. If skin irritation occurs: Get medical advice/attention.

**SE1180
CONSTRUCTION SEALANT****Inhalation**

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

NOTE TO PHYSICIAN

None known.

5. FIRE-FIGHTING MEASURES

Flash Point:	> 93.3 °C; 200 °F
Ignition Temperature:	No data available.
Autoignition Temperature:	<u>None</u>
Flammable Limits LEL:	No data available.
Flammable Limits UEL:	No data available.

SENSITIVITY TO MECHANICAL IMPACT: No

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

Extinguishing media

All standard extinguishing agents are suitable.

Special Fire Fighting Procedures

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES**ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED**

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

**SE1180
CONSTRUCTION SEALANT****7. HANDLING AND STORAGE****PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**

Use only in well-ventilated areas. Avoid contact with skin and eyes. Keep out of reach of children. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the finger and hands.

Storage

Keep away from heat, sparks and open flame.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Engineering controls**

Eye wash facilities and emergency shower must be available when handling this product.

Respiratory Protection

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

PROTECTIVE GLOVES

Cloth gloves.

EYE AND FACE PROTECTION

Safety glasses with side shields

Other protective equipment

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

<u>Component</u>	<u>CAS-No.</u>	<u>Source</u>	<u>Value</u>
------------------	----------------	---------------	--------------

Consult local authorities for acceptable provincial values.

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

**SE1180
CONSTRUCTION SEALANT****9. PHYSICAL AND CHEMICAL PROPERTIES**

Boiling point (°C):	Not applicable
VAPOR PRESSURE (20 C) (MM HG):	Not applicable
Vapor density (air=1):	<u>No data available.</u>
Freezing point:	Not applicable
Melting Point:	Not applicable
Physical State:	Solid
Odor:	Acetic acid.
Odor Threshold:	No data available.
Color:	White
Evaporation rate (Butyl Acetate=1):	< 1
Specific Gravity:	ca. 1.04
Density:	ca. 1.04 g/cm ³
ACID / ALKALINITY (MEQ/G):	Not applicable
pH:	Not applicable
VOLATILE ORGANIC CONTENT:	2.8 %(m)
SOLUBILITY IN WATER (20 C):	Insoluble
SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):	Toluene
Partition Coefficient: n-octanol/water:	No data available.

10. STABILITY AND REACTIVITY

Stability
Stable

HAZARDOUS POLYMERIZATION.
Hazardous polymerisation does not occur.

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS
Carbon dioxide; Formaldehyde.; Acetic acid.; Silicon dioxide.

Incompatible materials
None known.

Conditions to avoid
None known.

**SE1180
CONSTRUCTION SEALANT****11. TOXICOLOGICAL INFORMATION****ACUTE ORAL**

Remarks: No data available.

Repeated dose toxicityNone**ACUTE DERMAL**

Remarks: No data available.

Acute inhalation

Remarks: No data available.

Other

None.

Genetic Toxicity in vitroNone**Genetic toxicity in vivo**None**Sensitization**

Not applicable

Skin irritation.

Prolonged contact may cause redness and irritation.

EYE IRRITATION

Causes eye irritation.

Mutagenicity

No data available.

Other effects of overexposure

This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen.

Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

,Acetic acid released during curing.

12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available.

DISTRIBUTION

No data available.

**SE1180
CONSTRUCTION SEALANT**

CHEMICAL FATE

No data available.

13. DISPOSAL CONSIDERATIONS**Disposal Methods**

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION**Further Information:**

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION**Inventories**

Australia Inventory of Chemical Substances (AICS) y (positive listing)

EU list of existing chemical substances y (positive listing)

Japan Inventory of Existing & New Chemical Substances (ENCS) y (positive listing)

China Inventory of Existing Chemical Substances y (positive listing)

Korea Existing Chemicals Inventory (KECI) y (positive listing)

Canada DSL Inventory y (positive listing)

Canada NDSL Inventory n (Negative listing)

Philippines Inventory of Chemicals and Chemical Substances (PICCS) y (positive listing)

TSCA list y (positive listing)

On TSCA Inventory

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

Canadian Regulatory Information

**SE1180
CONSTRUCTION SEALANT**

WHMIS Classification
Toxic Material Causing Other Toxic Effects

CPR Compliance
This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

US Regulatory Information

SARA (311,312) HAZARD CLASS
Acute Health Hazard

SARA (313) CHEMICALS

16. OTHER INFORMATION**Other**

C = ceiling limit NEGL = negligible
EST = estimated NF = none found
NA = not applicable UNKN = unknown
NE = none established REC = recommended
ND = none determined V = recommended by vendor
SKN = skin TS = trade secret
R = recommended MST = mist
NT = not tested STEL = short term exposure limit
ppm = parts per million ppb = parts per billion
By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).

,These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.