



SAFETY DATA SHEET

Issuing Date 27-Oct-2014

Revision Date 15-Oct-2014

Revision Number 2

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product SDS Name Epoxy Putty Stick – High Heat

J-B Weld FG SKU Part Numbers Covered

8297, 8297F

J-B Weld Product Names Covered

HighHeat™ (all sizes)

J-B Weld Product Type

Epoxy Putty Stick

Recommended use of the chemical and restrictions on use

Recommended Use Adhesive & Repair

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name J-B WELD COMPANY, LLC
Supplier Address 1130 COMO ST
 SULPHUR SPRINGS, TX 75482
 USA

Emergency Telephone Numbers

Transportation Emergencies: Chemtrec (24 hour transportation emergency response info):
800-424-9300 or 703-527-3887

Poison/Medical Emergencies: Poison Control Centers (24 hour emergency poison / medical
response info): 800-222-1222

Supplier Email info@jbweld.com

Supplier Phone Number 903-885-7696

2. HAZARDS IDENTIFICATION

OSHA/HCS status

This material is considered hazardous by the OSHA Hazard Communication Standard (29-CFR 1910.1200).



Classification of the substance or mixture

SKIN SENSITIZATION – Category 1

GHS label elements

Hazard pictograms



Signal word

Warning!

Hazard statements

Causes skin and eye irritation.
May cause an allergic skin reaction.

Precautionary statements

General

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention

Wear protective gloves. Wear eye or face protection. Avoid breathing dust. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Response

IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage

Not applicable.

Disposal

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/mixture

Mixture

Ingredient name	% by weight	CAS number
Cristobalite	10-30	14464-46-1
crystalline silica non-respirable	10-30	14808-60-7

Canada

Name	CAS number	%
Talc, not containing asbestiform fibres	14807-96-6	10-30
Cristobalite	14464-46-1	10-30
glass, oxide, chemicals	65997-17-3	10-30
crystalline silica non-respirable	14808-60-7	10-30
3,6-diazaoctanethylenediamin	112-24-3	0.1-1

Occupational exposure limits, if available, are listed in Section 8.

4. FIRST AID MEASURES

Description of necessary first aid measure

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is regular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Skin contact	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Ingestion	Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Inhalation	Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Skin contact	May cause an allergic skin reaction.
Eye contact	No known significant effects or critical hazards.
Ingestion	No known significant effects or critical hazards.

Over-exposure signs/symptoms

Inhalation	No specific data.
Skin contact	Adverse symptoms may include the following: irritation redness
Eye contact	No specific data

Ingestion No specific data

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments No specific treatment.

See toxicological information (Section 11)

5. FIRE-FIGHTING MEASURES


Extinguishing media

Suitable extinguishing media Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media None known.

Specific hazards arising from the chemical No specific fire or explosion hazard.

National Fire Protection Association (U.S.A.)



Hazardous thermal decomposition products

Decomposition products may include the following materials:
Carbon dioxide
Carbon monoxide
Nitrogen oxides
Halogenated compounds
Metal oxide/oxides

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Avoid generation of dust. Do not breathe dust. Evacuate personnel to safe areas.

Other Information

Refer to protective measures listed in Sections 7 and 8.

Environmental Precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 35°C (95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Precautions for safe handling**Protective measure**

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measure.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational exposure limits

Ingredient name	CAS #	Exposure limits
cristobalite	14464-46-1	OSHA PEL Z3 (United States, 9/2005). Notes: 1/2[250/(%SiO₂+5)] TWA: 250 MPPCF / 2 x (%SiO₂+5) 8 hours. Form: Respirable OSHA PEL Z3 (United States, 9/2005). Notes: 1/2[10/(%SiO₂+2)] TWA: 10 MG/M³ / 2 x (%SiO₂+2) 8 hours. Form: Respirable OSHA PEL 1989 (United States, 3/1989). TWA: 0.05 mg/m³, (as quartz) 8 hours. Form: Respirable dust ACGIH TLV (United States, 3/2012). TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 1/2013). TWA: 0.05 mg/m³ 10 hours. Form: respirable dust OSHA PEL Z3 (United States, 9/2005). Notes: 1/2[30/(%SiO₂+2)] TWA: 30 MG/M³ / 2 x (%SiO₂+2) 8 hours. Form: Total dust.
crystalline silica non-respirable	14808-60-7	OSHA PEL Z3 (United States, 9/2005). Notes: 250/(%SiO₂+5) TWA: 250 MPPCF / (%SiO₂+5) 8 hours. Form: Respirable OSHA PEL Z3 (United States, 9/2005). Notes: 10/(SiO₂+2) TWA: 10 MG/M³ / (%SiO₂+2) 8 hours. Form: Respirable ACGIH TLV (United States, 3/2012). TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 1/2013). TWA: 0.05 mg/m³ 10 hours. Form: respirable dust OSHA PEL Z3 (United States, 9/2005). Notes: 30/(%SiO₂+2) TWA: 30 MG/M³ / (%SiO₂+2) 8 hours. Form: Total dust.

Canada

<u>Occupational exposure limits</u>	TWA (8 hours)	STEL (15 mins)	Ceiling	
-------------------------------------	---------------	----------------	---------	--

Ingredient	List name	ppm	mg/ m ³	Other	ppm	mg/ m ³	Other	ppm	mg/ m ³	Other	Notations
crystalline silica non-respirable	US ACGIH 3/2012	-	0.025	-	-	-	-	-	-	-	[a]
	BC 4/2012	-	0.025	-	-	-	-	-	-	-	[b]
	ON 1/2013	-	0.1	-	-	-	-	-	-	-	[c]
	QC 12/2012	-	0.1	-	-	-	-	-	-	-	[d]
cristobalite	US ACGIH 3/2012	-	0.025	-	-	-	-	-	-	-	[a]
	AB 4/2009	-	0.025	-	-	-	-	-	-	-	[e]
	BC 4/2012	-	0.025	-	-	-	-	-	-	-	[b]
	ON 1/2013	-	0.05	-	-	-	-	-	-	-	[c]
glass, oxide, chemicals	QC 12/2012	-	0.05	-	-	-	-	-	-	-	[d]
	US ACGIH 3/2012	-	5	-	-	-	-	-	-	-	[f]
	US ACGIH 3/2012	-	-	1 f/cc	-	-	-	-	-	-	[g]
	AB 4/2009	-	5	1 f/cc	-	-	-	-	-	-	[h]
		-	5	-	-	-	-	-	-	-	[i]
	BC 4/2012	-	5	-	-	-	-	-	-	-	[j]
		-	-	1 f/cc	-	-	-	-	-	-	
	ON 1/2013	-	10	-	-	-	-	-	-	-	[k]
		-	5	-	-	-	-	-	-	-	[l]
		-	-	1 f/cc	-	-	-	-	-	-	[m]
	QC 12/2012	-	-	1 f/cc	-	-	-	-	-	-	[n]
		-	10	-	-	-	-	-	-	-	[o]
Talc , not containing asbestiform fibres	AB 4/2009	-	2	-	-	-	-	-	-	-	[e]
	BC 4/2012	-	2	-	-	-	-	-	-	-	[b]
		-	-	0.1 f/cc	-	-	-	-	-	-	
	ON 1/2013	-	2	-	-	-	-	-	-	-	[c]
		-	2	-	-	-	-	-	-	-	[p]
		-	-	2 f/cc	-	-	-	-	-	-	
	QC 12/2012	-	3	-	-	-	-	-	-	-	[d]
	ON 1/2013	0.5	3	-	-	-	-	-	-	-	[1]
3,6-diazaoctanethylenediamin	US AIHA 10/2011	1	-	-	-	-	-	-	-	-	[1]

Form: [a]Respirable particulate [b]Respirable [c]Respirable fraction: means that size fraction of the airborne particulate deposited in the gas-exchange region of the respiratory tract and collected during air sampling with a particle size- selective device that, (a) meets the ACGIH particle size–selective sampling criteria for airborne particulate matter; and (b) has the cut point of 4 µm at 50 per cent collection efficiency. [d]The value is for particulate matter containing no asbestos and < 1 per cent crystalline silica. [e]Respirable dust. [f]Inhalable fraction [g]Respirable fibers: length greater than 5 µm; aspect ratio equal to or greater than 3:1 as determined by the membrane filter method at 400-450X magnification (4-mm objective) phase contrast illumination. [h]Fibres [i]Fibres, total particulate [j]Inhalable [k]Fiber [l]Inhalable fraction: means that size fraction of the airborne particulate deposited anywhere in the respiratory tract and collected during air sampling with a particle size-selective device that, (a) meets the ACGIH particle size-selective sampling criteria for airborne particulate matter; and (b) has the cut point of 100 µm at 50 per cent collection efficiency. [m]Respirable fibres: length > 5µm; aspect ratio ≥3:1, as determined by the membrane filter method at 400-450 times magnification (4-mm objective), using phase-contrast illumination. [n]RESPIRABLE FIBRES (other than respirable asbestos fibres) : Objects, other than respirable asbestos fibres, longer than 5 µm, having a diameter of less than 3 µm and a ratio of length to diameter of more than 3 :1. [o]Total dust. [p]Respirable fraction [q]Total dust

Appropriate engineering controls

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures**Hygiene measures**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Skin Protection**Hand protection**

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties**Physical State**

Solid

Appearance

Metallic. Gray-Beige

Color

Metallic. Gray-Beige

Odor

Ethereal

Odor Threshold

No information available

Property**Values****Remarks/ Method****pH**

No data available

None known

Melting / freezing point

No data available

None known

Boiling point / boiling range

No data available

None known

Flash Point

Closed cup: >93° C

None known

Evaporation Rate

No data available

None known

Flammability (solid, gas)

Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.

None known

Flammability Limit in Air**Upper flammability limit**

No data available

Lower flammability limit

No data available

Vapor pressure

No data available

None known

Vapor density

No data available

None known

Specific Gravity	1.741	None known
Water Solubility	Insoluble in water	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	>200° C	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	
Oxidizing Properties	No data available	
<u>Other Information</u>		

Softening Point	No data available
VOC Content (%)	0
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity

No specific data.

Irritation/Corrosion

No specific data

Sensitization

No specific data.

Mutagenicity

No specific data.

Carcinogenicity

No specific data.



<u>Classification</u>			
Product/ingredient name	OSHA	IARC	NTP
cristobalite	-	1	Known to be a human carcinogen.
Crystalline silica non-respirable	-	1	Known to be a human carcinogen.

Reproductive toxicity

No specific data

Teratogenicity

No specific data.

Specific target organ toxicity (single exposure)

No specific data.

Specific target organ toxicity (repeated exposure)

No specific data.

Aspiration hazard

No specific data.

Information on the likely routes of exposure

Not available

Potential acute health effects**Eye contact**

No known significant effects or critical hazards.

Inhalation

Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

Skin contact

May cause an allergic skin reaction.

Ingestion

No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics**Eye contact**

No specific data

Inhalation

No specific data.

Skin contactAdverse symptoms may include the following:
irritation
redness**Ingestion**

No specific data

Delayed and immediate effects and also chronic effects from short and long term exposure**Short term exposure****Potential immediate effects**

Not available

Potential delayed effects

Not available

Long term exposure**Potential immediate effects**

Not available

Potential delayed effects

Not available

Potential chronic health effects

No specific data.

General

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

No known significant effects or critical hazards.

Teratogenicity

No known significant effects or critical hazards.

Developmental effects

No known significant effects or critical hazards.

Fertility effects

No known significant effects or critical hazards.

Numerical measures of toxicity**Acute toxicity estimates**

No specific data.

12. ECOLOGICAL INFORMATION

Toxicity	No specific data.
Persistence and degradability	No specific data.
<u>Bioaccumulative potential</u>	No specific data.
<u>Mobility in soil</u>	
Soil/water partition coefficient (K_{oc})	Not available
Other adverse effects	No known significant effects or critical hazards.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

14. TRANSPORT INFORMATION

<u>DOT</u>	NOT REGULATED
Proper Shipping Name	NON REGULATED
Hazard Class	N/A
Marine Pollutant	This product contains a chemical which is listed as a marine pollutant according to DOT
<u>TDG</u>	Not regulated
<u>MEX</u>	Not regulated
<u>ICAO</u>	Not regulated
<u>IATA</u>	Not regulated
Proper Shipping Name	NON REGULATED
Hazard Class	N/A
<u>IMDG/IMO</u>	Not regulated
Hazard Class	N/A
Marine Pollutant	Product is a marine pollutant according to the criteria set by IMDG/IMO
<u>RID</u>	Not regulated
<u>ADR</u>	Not regulated
<u>ADN</u>	Not regulated

15. REGULATORY INFORMATION

United States

U.S. Federal regulations

TSCA 8(a) PAIR: Siloxanes and Silicones, di-Me, reaction products with silica
TSCA 8(a) CDR Exempt/Partial exemption: Not determined
United States inventory (TSCA 8b): All components are listed or exempted.

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)

Not listed

Clean Air Act Section 602 Class I Substances

Not listed

Clean Air Act Section 602 Class II Substances

Not listed

SARA 302/304

Composition/information on ingredients

No products were found

SARA 304 RQ

Not applicable

SARA 311/312

Classification

Immediate (acute) health hazard

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Cristobalite	10-30	No.	No.	No.	No.	Yes
crystalline silica non-respirable	10-30	No.	No.	No.	No.	Yes

State regulations

Massachusetts

The following components are listed: SOAPSTONE; MINERAL WOOL FIBER

New York

None of the components are listed.

New Jersey

The following components are listed: SOAPSTONE, SILICA, QUARTZ; QUARTZ (SiO₂); FERROSILICON; FERROCERIUM

Pennsylvania

The following components are listed: SOAPSTONE DUST, QUARTZ (SiO₂)

Minnesota Hazardous Substances

None of the components are listed.

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer

Ingredient Name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Talc, not containing asbestiform fibres	Yes.	No.	No.	No.
cristobalite	Yes.	No.	No.	No.
Crystalline silica non-respirable	Yes.	No.	No	No

Canada

WHMIS (Canada) Class D-2A: Material causing other toxic effects (Very toxic).

Canadian lists

Canadian NPRI None of the components are listed.

CEPA Toxic substances None of the components are listed.

Canada inventory All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

International lists

Australia inventory (AICS): All components are listed or exempted.
China inventory (IECSC): Not determined.
Japan inventory: Not determined.
Korea inventory: All components are listed or exempted.
Malaysia Inventory (EHS Register): Not determined.
New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.
Philippines inventory (PICCS): All components are listed or exempted.
Taiwan inventory (CSNN): Not determined.

Substances of very high concern None of the components are listed.

16. OTHER INFORMATION

Key to abbreviations

ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations

Notice to reader

NON-WARRANTY: The information presented in this publication is based upon the research and experience of J-B Weld Company. No representation or warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. J-B Weld Company makes no warranty or representation of any kind, express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by J-B Weld Company are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose particular to the buyers is for the buyer to determine. J-B Weld Company assumed no responsibility for the selection of products suitable to the particular purposes of any particular buyer. J-B Weld Company shall in no event be liable for any special, incidental, or consequential damages.

End of Safety Data Sheet

