

Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 07.12.2019

Page 1 of 14

Steel Reinforced Epoxy Hardener - Fast Cure - Part B

SECTION 1: Identification

Product identifier

Product name: Steel Reinforced Epoxy Hardener - Fast Cure - Part B

Product code: 50176 - Part B CAN



Recommended use of the product and restriction on use

Relevant identified uses: Not determined or not applicable.

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

North America

J-B Weld Company, LLC

400 CMH Road

Sulphur Springs, TX 75482

903-885-7696

info@jbweld.com

Emergency telephone number:

North America

CHEMTREC

1-800-424-9300 (24 hour)

SECTION 2: Hazard identification

GHS classification:

Skin corrosion, category 1B

Serious eye damage, category 1

Skin sensitization, category 1

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

Precautionary statements:

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash hands thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 07.12.2019

Page 2 of 14

Steel Reinforced Epoxy Hardener - Fast Cure - Part B

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see supplemental first aid instructions on this label).

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor/physician.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 14807-96-6	Talc	1-5
CAS number: 14808-60-7	Silica, crystalline quartz	0.02
CAS number: 112-57-2	1,2-Ethanediamine, N1-(2-aminoethyl)-N2-[2-[(2-aminoethyl)amino]ethyl]-	0.1-1
CAS number: 112-24-3	Triethylenetetramine	0.1-1
CAS number: 13463-67-7	Titanium Dioxide	0.1-1
CAS number: 90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	5-10
CAS number: 21645-51-2	Aluminum hydroxide	0.02
CAS number: 7631-86-9	Silicon Dioxide	0.02
CAS number: 1314-23-4	Zirconium dioxide	0.01
CAS number: 72244-98-5	Poly(oxy(methyl-1,2-ethanediyl)), alpha-hydro-omega-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	45-70
CAS number: 68131-73-7	Amines, polyethylenepoly-; HEP	1-5
CAS number: 4067-16-7	3,6,9,12-tetra-azatetradecamethylenediamine; Pentaethylenehexamine	1-5

Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 07.12.2019

Page 3 of 14

Steel Reinforced Epoxy Hardener - Fast Cure - Part B

Additional Information:

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with the Canadian Hazardous Products Regulation and WHMIS 2015.

SECTION 4: First-aid measures

Description of first-aid measures

General notes:

Not determined or not available.

After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention

After skin contact:

Treatment is urgent. Seek emergency medical treatment. Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse

After eye contact:

Immediately rinse eyes with plenty of gently flowing lukewarm water for 15 minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. Seek immediate medical attention, preferably from an ophthalmologist

After ingestion:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Exposure to skin may result in redness, pain, burning, inflammation and tissue damage. Exposure to eyes may result in irritation, redness, pain, inflammation, itching, burning and tearing. Exposure via inhalation may result in cough, sore throat, burning sensation and shortness of breath. Exposure via ingestion may result in burns of the mouth and throat, abdominal pain, burning sensation in the throat and chest, nausea, vomiting, shock or collapse

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time)

Immediate medical attention and special treatment

Specific treatment:

Not determined or not available.

Notes for the doctor:

Treat symptomatically

SECTION 5: Fire-fighting measures

Extinguishing media

Suitable extinguishing media:

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition

Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 07.12.2019

Page 4 of 14

Steel Reinforced Epoxy Hardener - Fast Cure - Part B

Unsuitable extinguishing media:

Not determined or not applicable.

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

Carbon monoxide and carbon dioxide may form upon combustion

Heating causes a rise in pressure, risk of bursting and combustion

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

Wear recommended personal protective equipment (see Section 8)

Environmental precautions:

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing

Sweep or scoop up solid material while minimizing dust generation

Dispose of contents / container in accordance with local regulations

Reference to other sections:

Section 8: Personal Protective Equipment

SECTION 7: Handling and storage

Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing dust.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Wear recommended personal protective equipment (see Section 8).

Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.

Keep container dry.

Store in a cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 07.12.2019

Page 5 of 14

Steel Reinforced Epoxy Hardener - Fast Cure - Part B

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Canada	Triethylenetetramine	112-24-3	Ontario: 8-hour TWA 3.0 mg/m ³ (0.5 ppm)
	Silicon Dioxide	7631-86-9	British Columbia OELs - 8-Hour TWA Exposure Value: 4 mg/m ³ (Silica, amorphous, precipitated and gel, Total)
	Silicon Dioxide	7631-86-9	British Columbia OELs - 8-Hour TWA Exposure Value: 1.5 mg/m ³ (Silica, amorphous, precipitated and gel, Respirable)
	Silicon Dioxide	7631-86-9	Quebec OELs - 8-Hour TWA Exposure Value: 6 mg/m ³ (Respirable dust)
	Titanium Dioxide	13463-67-7	Alberta OEL: TWA 10 mg/m ³ 8-hr
	Silica, crystalline quartz	14808-60-7	Alberta OELs - 8-Hour TWA Exposure Limit: 0.025 mg/m ³ (respirable)
	Silica, crystalline quartz	14808-60-7	British Columbia OELs - 8-Hour TWA Exposure Value: 0.025 mg/m ³ (respirable)
	Titanium Dioxide	13463-67-7	British Columbia OEL: TWA 10 mg/m ³ (Total dust) 8-hr
	Titanium Dioxide	13463-67-7	British Columbia OEL: TWA 3.0 mg/m ³ (Respirable fraction) 8-hr
	Silica, crystalline quartz	14808-60-7	Manitoba OELs - 8-Hour TWA Exposure Limit: 0.025 mg/m ³ (respirable fraction)
	Titanium Dioxide	13463-67-7	Manitoba OEL: TLV-TWA 10 mg/m ³ 8-hr
	Silica, crystalline quartz	14808-60-7	Ontario OELs - 8-Hour TWA Exposure Limit: 0.10 mg/m ³ (respirable fraction)
	Silica, crystalline quartz	14808-60-7	Quebec OELs - 8-Hour TWA Exposure Value: 0.1 mg/m ³ (respirable)
	Titanium Dioxide	13463-67-7	Ontario OEL: TWA 10 mg/m ³ 8-hr
	Titanium Dioxide	13463-67-7	Quebec OEL: TWA 10 mg/m ³ 8-hr
	Silica, crystalline quartz	14808-60-7	Saskatchewan OELs - 15 Minute Average Contamination Limit: 0.05 mg/m ³ (respirable fraction)
	Titanium Dioxide	13463-67-7	Saskatchewan OEL: TWA 10 mg/m ³ 8-hr
	Zirconium dioxide	1314-23-4	Alberta OELs - 8-Hour TWA Exposure Limit: 5 mg/m ³
	Titanium Dioxide	13463-67-7	Saskatchewan OEL: TWA 20 mg/m ³ 15-min
	Zirconium dioxide	1314-23-4	Alberta OELs -15-minute STEL: 10 mg/m ³
Zirconium dioxide	1314-23-4	Manitoba OELs - 8-Hour Exposure Limit (TLV-TWA): 5 mg/m ³	

Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 07.12.2019

Page 6 of 14

Steel Reinforced Epoxy Hardener - Fast Cure - Part B

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Zirconium dioxide	1314-23-4	Manitoba OELs - 15-minute STEL: 10 mg/m ³
	Zirconium dioxide	1314-23-4	Ontario OELs - 8-Hour TWA Exposure Value (TWA): 5 mg/m ³
	Zirconium dioxide	1314-23-4	Ontario OELs - 15-minute STEL (STEL): 10 mg/m ³
	Zirconium dioxide	1314-23-4	Quebec OELs - 8-Hour TWA Exposure Value: 5 mg/m ³
	Zirconium dioxide	1314-23-4	Quebec OELs - 15-minute STEL: 10 mg/m ³
	Zirconium dioxide	1314-23-4	Saskatchewan OELs - 8 hour average contamination limit: 5 mg/m ³
	Zirconium dioxide	1314-23-4	Saskatchewan OELs - 15 minute average contamination limit: 10 mg/m ³
	Talc	14807-96-6	Alberta OELs - 8- hour TWA Exposure Limit: 2 mg/m ³
	Talc	14807-96-6	British Columbia OELs - 8-Hour TWA Exposure Value: 2 mg/m ³ (respirable)
	Talc	14807-96-6	Manitoba OELs - 8-Hour Exposure Limit (TLV-TWA): 2 mg/m ³ (respirable fraction)
	Talc	14807-96-6	Ontario OELs - 8-Hour TWA Exposure Value (TWA): 2 mg/m ³ (respirable fraction)
	Talc	14807-96-6	Quebec OELs - 8-Hour TWA Exposure Value: 3 mg/m ³ (respirable fraction)
	Talc	14807-96-6	Saskatchewan OELs - 8 Hour Average Contamination Limit: 2 mg/m ³ (respirable fraction)
	Aluminum hydroxide	21645-51-2	Alberta OELs - 8-Hour TWA Exposure Limit: 10 mg/m ³
	Aluminum hydroxide	21645-51-2	Alberta OELs - 8-Hour TWA Exposure Limit: 3 mg/m ³ (Respirable)
	Aluminum hydroxide	21645-51-2	British Columbia OELs - 8-Hour TWA Exposure Value: 1 mg/m ³ (Respirable)
	Aluminum hydroxide	21645-51-2	British Columbia OELs - 8-Hour TWA Exposure Value: 10 mg/m ³ (Total Dust)
	Aluminum hydroxide	21645-51-2	British Columbia OELs - 8-Hour TWA Exposure Value: 3 mg/m ³ (Respirable Fraction)
	Aluminum hydroxide	21645-51-2	Manitoba OELs - Hour Exposure Limit (TLV-TWA): 1 mg/m ³ (Respirable fraction)

Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 07.12.2019

Page 7 of 14

Steel Reinforced Epoxy Hardener - Fast Cure - Part B

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Aluminum hydroxide	21645-51-2	Ontario OELs - 8-Hour TWA Exposure Value (TWA): 1 mg/m ³ (Respirable fraction)
	Aluminum hydroxide	21645-51-2	Ontario OELs - 8-Hour TWA Exposure Value (TWA): 10 mg/m ³ (Particles (poorly soluble or insoluble) not otherwise classified, Inhalable fraction)
	Aluminum hydroxide	21645-51-2	Ontario OELs - 8-Hour TWA Exposure Value (TWA): 3 mg/m ³ (Particles (poorly soluble or insoluble) not otherwise classified, Respirable fraction)
	Aluminum hydroxide	21645-51-2	Quebec OELs - 8-Hour TWA Exposure Value: 10 mg/m ³ (Total dust)
	Aluminum hydroxide	21645-51-2	Saskatchewan OELs - 8 Hour Average Contamination Limit: 10 mg/m ³ (Metal dust and compounds as Al)
	Aluminum hydroxide	21645-51-2	Saskatchewan OELs - 15 minute average contamination limit: 20 mg/m ³ (Metal dust and compounds as Al)
	Aluminum hydroxide	21645-51-2	Saskatchewan OELs - 8 hour average contamination limit: 3 mg/m ³ (Particles (poorly soluble or insoluble) not otherwise classified, Respirable fraction)
	Aluminum hydroxide	21645-51-2	Saskatchewan OELs - 15 minute average contamination limit: 6 mg/m ³ (Particles (poorly soluble or insoluble) not otherwise classified, Respirable fraction)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.

Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 07.12.2019

Page 8 of 14

Steel Reinforced Epoxy Hardener - Fast Cure - Part B

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance (physical state, color):	White solid
Odor:	Pungent. Sulfurous. (Strong)
Odor threshold:	Not determined or not available.
pH-value:	Not determined or not available.
Melting/Freezing point:	Not determined or not available.
Boiling point/range:	Not determined or not available.
Flash point:	Closed cup: >93.3°C (>199.9°F) [Setaflash]. Product does not sustain combustion.
Evaporation rate:	Not determined or not available.
Flammability (solid, gaseous):	Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.
Explosion limit upper:	Not determined or not available.
Explosion limit lower:	Not determined or not available.
Vapor pressure:	Not determined or not available.
Vapor density:	1.199
Density:	Not determined or not available.
Relative density:	1.2
Solubilities:	Not determined or not available.
Partition coefficient (n-octanol/water):	Not determined or not available.
Auto/Self-ignition temperature:	>200°C (>392°F)
Decomposition temperature:	>200°C (>392°F)
Dynamic viscosity:	Not determined or not available.
Kinematic viscosity:	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

Other information

VOC Content (%)	<3%
------------------------	-----

SECTION 10: Stability and reactivity

Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 07.12.2019

Page 9 of 14

Steel Reinforced Epoxy Hardener - Fast Cure - Part B

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

Open flames, sparks and static discharge.

Incompatible materials:

None known.

Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
2,4,6-tris(dimethylaminomethyl)phenol	oral	LD50 - Rat - 1,200 mg/kg
Aluminum hydroxide	oral	LD50 Rat: >5000 mg/kg
	inhalation	LC50 (4 h): 888 - 2,300 mg/m ³ air (rat)

Skin corrosion/irritation

Assessment:

Causes severe skin burns and eye damage

Product data:

No data available.

Substance data:

Name	Result
1,2-Ethanediamine, N1-(2-aminoethyl)-N2-[2-[(2-aminoethyl)amino]ethyl]-	Causes severe skin burns and eye damage.
2,4,6-tris(dimethylaminomethyl)phenol	Causes skin irritation.
Amines, polyethylenepoly-; HEP	Causes severe skin burns and eye damage.
3,6,9,12-tetra-azatetradecamethylenediamine ; Pentaethylenehexamine	Causes severe skin burns and eye damage.
Triethylenetetramine	Causes severe skin burns and eye damage.

Serious eye damage/irritation

Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 07.12.2019

Page 10 of 14

Steel Reinforced Epoxy Hardener - Fast Cure - Part B

Assessment:

Causes serious eye damage

Product data:

No data available.

Substance data:

Name	Result
2,4,6-tris(dimethylaminomethyl)phenol	Causes serious eye irritation.

Respiratory or skin sensitization

Assessment:

May cause an allergic skin reaction

Product data:

No data available.

Substance data:

Name	Result
Poly(oxy(methyl-1,2-ethanediyl)), alpha-hydro-omega-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	May cause an allergic skin reaction.
Amines, polyethylenepoly-; HEP	May cause an allergic skin reaction.
1,2-Ethanediamine, N1-(2-aminoethyl)-N2-[2-[(2-aminoethyl)amino]ethyl]-	May cause an allergic skin reaction.
3,6,9,12-tetra-azatetradecamethylenediamine ; Pentaethylenehexamine	May cause an allergic skin reaction.
Triethylenetetramine	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Species	Result
Titanium Dioxide	Not applicable.	Airborne, unbound particles of respirable size are known to cause cancer.
Silica, crystalline quartz	Not applicable	Component may cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Talc	Group 3 - Not classifiable as to its carcinogenicity to humans
Titanium Dioxide	Group 2B
Silica, crystalline quartz	Group 1 - Carcinogenic to humans
Silicon Dioxide	Group 3 - Not classifiable as to its carcinogenicity to humans

Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 07.12.2019

Page 11 of 14

Steel Reinforced Epoxy Hardener - Fast Cure - Part B

National Toxicology Program (NTP):

Name	Classification
Silica, crystalline quartz	Known to be human carcinogens

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Silica, crystalline quartz	Component affects the lungs through repeated exposure.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment:

Toxic to aquatic life

Product data: No data available.

Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 07.12.2019

Page 12 of 14

Steel Reinforced Epoxy Hardener - Fast Cure - Part B

Substance data:

Name	Result
Triethylenetetramine	LC50 - Daphnia magna (Water flea) - 33.9 mg/L - 48 h
Aluminum hydroxide	LC50 (16 days): 430 - 3,910 µg/L
	NOEC (33 days): 71.5 - 558.1 µg/L
	EC50 (48 h): 1.5 - 2.56 mg/L

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Poly(oxy(methyl-1,2-ethanediyl)), alpha-hydro-omega-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	NOEC - Daphnia magna (Water flea) - 3.5 mg/L - 21 d

Persistence and degradability

Product data: No data available.

Substance data: No data available.

Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

Canadian Transportation of Dangerous Goods (TDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	In accordance with Section 1.45.1 (SOR/2008-34) of the TDG Regulations, this product is not regulated as a marine pollutant as it is transported solely on land by road vehicle or railway vehicle.

Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 07.12.2019

Page 13 of 14

Steel Reinforced Epoxy Hardener - Fast Cure - Part B

Special precautions for user	None
Additional Information	Non-bulk packages of this product are not regulated as hazardous materials unless transported by inland waterway. This product is not regulated as a hazardous material as it is transported in sizes of ≤ 5 kg and the packagings meet the general provisions of Section 1.17 (SOR/2008-34) of the TDG Regulations.

International Maritime Dangerous Goods (IMDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	This material is shipped in quantities of less than 5 kg and as such does not need to be marked as an Environmentally Hazardous Substance.
Special precautions for user	None
Additional Information	This product is not regulated as a dangerous good as it is transported in sizes of ≤ 5 kg and the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. Additionally, this product transported solely on land by road vehicle or railway vehicle.

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	This material is shipped in quantities of less than 5 kg and as such does not need to be marked as an Environmentally Hazardous Substance.
Special precautions for user	None
Additional Information	This product is not regulated as a dangerous good as it is transported in sizes of ≤ 5 kg and the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8. Additionally, this product transported solely on land by road vehicle or railway vehicle.

SECTION 15: Regulatory information

Canada regulations

Domestic substances list (DSL):

72244-98-5	Poly(oxy(methyl-1,2-ethanediyl)), alpha-hydro-omega-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	Listed
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	Listed

Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 07.12.2019

Page 14 of 14

Steel Reinforced Epoxy Hardener - Fast Cure - Part B

68131-73-7	Amines, polyethylenepoly-; HEP	Listed
4067-16-7	3,6,9,12-tetra-azatetradecamethylenediamine; Pentaethylenehexamine	Listed
14807-96-6	Talc	Listed
13463-67-7	Titanium Dioxide	Listed
112-57-2	1,2-Ethanediamine, N1-(2-aminoethyl)-N2-[2-[(2-aminoethyl)amino]ethyl]-	Listed
112-24-3	Triethylenetetramine	Listed
14808-60-7	Silica, crystalline quartz	Listed
21645-51-2	Aluminum hydroxide	Listed
7631-86-9	Silicon Dioxide	Listed
1314-23-4	Zirconium dioxide	Listed

Non-domestic substances list (NDSL): None of the ingredients are listed.

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with the Canadian Hazardous Products Regulations and WHMIS 2015. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial preparation date: 07.12.2019

End of Safety Data Sheet