



Blaster Rust Neutralizer

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)
Issue date: 2024-07-26 Revision date: 2024-07-26 Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
Product name : Blaster Rust Neutralizer
Product code : 16-RN-CND

1.2. Recommended use and restrictions on use

Recommended use : Adhesive

1.3. Supplier

Supplier

The Blaster Corporation
8500 Sweet Valley Drive
Valley View, Ohio, USA, 44125
USA
T (216) 901-5800 - F (216) 901-5801
www.blastercorp.com

Distributor

Princess Auto
475 Panet Road
Winnipeg, MB R2C 2Z1
Canada
Tel: (204) 667-4630

1.4. Emergency telephone number

Emergency number : ChemTel 800-255-3924

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Flam. Aerosol 1	H222	Extremely flammable aerosol.
Press. Gas (Liq.)	H280	Contains gas under pressure; may explode if heated.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2A	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Hazard pictograms (GHS-CA) :



Signal word (GHS CA) : Danger

Hazard statements (GHS-CA) :

H222 - Extremely flammable aerosol.
H280 - Contains gas under pressure; may explode if heated.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Precautionary statements (GHS-CA) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Blaster Rust Neutralizer

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312 - Call a POISON CENTER or doctor if you feel unwell.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
Acetone	-	CAS-No.: 67-64-1	15 - 40	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Formic acid	-	CAS-No.: 64-18-6	< 3	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Inhalation), H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 HHNOC 1, HHNOC
Tannins [Gallic acid derivatives found in nutgalls, bark and other plant parts, especially oak bark.]	-	CAS-No.: 1401-55-4	0.5 - 1.5	Eye Irrit. 2A, H319

Blaster Rust Neutralizer

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS CA)
2-butoxyethanol	-	CAS-No.: 111-76-2	0.1 – 1	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 1, H372

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	--

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Carbon dioxide, dry chemical, foam, water spray, fog.
------------------------------	---

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	: Do not use water jet.
--------------------------------	-------------------------

5.3. Specific hazards arising from the hazardous product

Fire hazard	: Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Irritating vapours.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Ruptured cylinders may rocket.

Blaster Rust Neutralizer

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

5.4. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. DO NOT fight fire when fire reaches explosives.
- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges. Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Methods and materials for containment and cleaning up

- For containment : Remove ignition sources. Stop leak if safe to do so. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate PPE (see Section 8).
- Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.
- Additional hazards when processed : Hazardous waste due to potential risk of explosion.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep out of the reach of children. Keep container tightly closed. Keep in fireproof place. Store in a dry, cool and well-ventilated place. Store away from direct sunlight or other heat sources. Do not expose to temperatures exceeding 50 °C/ 122 °F. Protect containers from physical damage.
- Incompatible products : Refer to Section 10 on Incompatible Materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-butoxyethanol (111-76-2)

USA - ACGIH - Occupational Exposure Limits

Local name	2-Butoxyethanol (EGBE)
ACGIH OEL TWA	20 ppm

Blaster Rust Neutralizer

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

2-butoxyethanol (111-76-2)	
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2020
USA - ACGIH - Biological Exposure Indices	
BEI	200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift
USA - OSHA - Occupational Exposure Limits	
Local name	2-Butoxyethanol
OSHA PEL TWA	240 mg/m³
OSHA PEL TWA	50 ppm
Limit value category (OSHA)	prevent or reduce skin absorption
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Acetone (67-64-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Acetone
ACGIH OEL TWA	250 ppm
ACGIH OEL STEL	500 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2024
USA - ACGIH - Biological Exposure Indices	
Local name	Acetone
BEI	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift (nonspecific)
Regulatory reference	ACGIH 2024
USA - OSHA - Occupational Exposure Limits	
Local name	Acetone
OSHA PEL TWA	2400 mg/m³
OSHA PEL TWA	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Formic acid (64-18-6)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	5 ppm
ACGIH OEL STEL	10 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	9 mg/m³
OSHA PEL TWA	5 ppm

Blaster Rust Neutralizer

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness.

Eye protection:

Wear eye/face protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol
Colour	: Clear
Odour	: Pleasant
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: -41 °C (Dimethyl ether)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapour pressure	: 42.7×10^4 (Dimethyl ether)
Relative vapour density at 20°C	: 1.6 (Dimethyl ether)
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: 3.4 – 18 vol % (Dimethyl ether)

Blaster Rust Neutralizer

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Tannins [Gallic acid derivatives found in nutgalls, bark and other plant parts, especially oak bark.] (1401-55-4)	
Flash point	199 °C (open cup)
Auto-ignition temperature	526.67 °C

2-butoxyethanol (111-76-2)	
Boiling point	(>171 - <171.5 °C - at 1 atm)
Flash point	67 °C (closed cup)
Auto-ignition temperature	230 °C
Vapour pressure	0.8 hPa Temp.: 20 °C

Acetone (67-64-1)	
Boiling point	56.05 °C (at 1013.25 hPa)
Flash point	-20 °C
Auto-ignition temperature	465 °C
Vapour pressure	233 hPa (at 20 °C)

Formic acid (64-18-6)	
Boiling point	100.23 °C (at 1013.25 hPa)
Flash point	46.5 °C (closed cup)
Auto-ignition temperature	539 °C
Vapour pressure	170.7 hPa (at 50 °C)

9.2. Other information

VOC content : ~51 %
Gas group : Press. Gas (Liq.)

SECTION 10: Stability and reactivity

Reactivity : No dangerous reactions known under normal conditions of use.
Chemical stability : Stable under normal conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.
Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.
Conditions to avoid : Heat. Sparks. Open flame. Direct sunlight. Overheating. Incompatible materials.
Incompatible materials : Strong acids. Strong oxidizers. Strong bases. Strong reducing agents. Peroxides. Ammonia. Amines. Chlorine. Halogens.
Hazardous decomposition products : May include, and are not limited to: oxides of carbon.
Hardening time: : No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified.

Blaster Rust Neutralizer

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Tannins [Gallic acid derivatives found in nutgalls, bark and other plant parts, especially oak bark.] (1401-55-4)	
LD50 oral rat	2260 mg/kg bodyweight Animal: rat
ATE CA (oral)	2260 mg/kg bodyweight
2-butoxyethanol (111-76-2)	
LD50 oral rat	1200 mg/kg
LD50 oral	1414 mg/kg bodyweight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961
LD50 dermal rabbit	435 mg/kg (Source: OECD_SIDS)
LC50 inhalation rat	3 mg/l
LC50 inhalation rat	486 ppm/4h
ATE CA (oral)	1200 mg/kg bodyweight
ATE CA (Dermal)	435 mg/kg bodyweight
ATE CA (Gases)	486 ppmv/4h
ATE CA (vapours)	3 mg/l/4h
ATE CA (dust,mist)	3 mg/l/4h
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 15700 mg/kg (Source: OECD_SIDS)
LC50 inhalation rat	50100 mg/m³ (Exposure time: 8 h Source: OECD_SIDS)
ATE CA (oral)	5800 mg/kg bodyweight
ATE CA (vapours)	50.1 mg/l/4h
ATE CA (dust,mist)	50.1 mg/l/4h
Formic acid (64-18-6)	
LD50 oral rat	1100 mg/kg (Source: NLM_CIP)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation rat	7.85 mg/l/4h
ATE CA (oral)	1100 mg/kg bodyweight
ATE CA (Gases)	700 ppmv/4h
ATE CA (vapours)	7.85 mg/l/4h
ATE CA (dust,mist)	0.5 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Tannins [Gallic acid derivatives found in nutgalls, bark and other plant parts, especially oak bark.] (1401-55-4)	
IARC group	3 - Not classifiable
2-butoxyethanol (111-76-2)	
IARC group	3 - Not classifiable

Blaster Rust Neutralizer

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Formic acid (64-18-6)	
NOAEL (chronic, oral, animal/male, 2 years)	400 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Remarks on results: other:Effect type: toxicity (migrated information)
Reproductive toxicity	: Not classified.
Acetone (67-64-1)	
LOAEL (animal/female, F0/P)	11298 mg/kg bodyweight Animal: mouse, Animal sex: female
NOAEL (animal/male, F0/P)	900 mg/kg bodyweight Animal: rat, Animal sex: male
STOT-single exposure	: May cause drowsiness or dizziness.
2-butoxyethanol (111-76-2)	
STOT-single exposure	May cause respiratory irritation.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified.
2-butoxyethanol (111-76-2)	
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study), Remarks on results: other:
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Formic acid (64-18-6)	
LOAEL (oral, rat, 90 days)	2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
NOAEL (oral, rat, 90 days)	400 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.244 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Aspiration hazard	: Not classified.
Blaster Rust Neutralizer	
Vaporizer	Aerosol
Tannins [Gallic acid derivatives found in nutgalls, bark and other plant parts, especially oak bark.] (1401-55-4)	
Animal studies and expert judgment for classification	False
2-butoxyethanol (111-76-2)	
Animal studies and expert judgment for classification	False
Acetone (67-64-1)	
Animal studies and expert judgment for classification	False
Formic acid (64-18-6)	
Animal studies and expert judgment for classification	False
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract. May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Blaster Rust Neutralizer

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.
Hazardous to the aquatic environment, short-term (acute) : Not classified.
Hazardous to the aquatic environment, long-term (chronic) : Not classified.

Tannins [Gallic acid derivatives found in nutgalls, bark and other plant parts, especially oak bark.] (1401-55-4)	
LC50 - Fish [1]	37 mg/l Test organisms (species): Gambusia affinis
EC50 - Other aquatic organisms [1]	29 mg/l Test organisms (species): other aquatic mollusc:
2-butoxyethanol (111-76-2)	
LC50 - Fish [1]	1474 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus Source: IUCLID)
EC50 - Crustacea [1]	≈ 1800 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	911 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	1840 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC chronic fish	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '21 d'
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Acetone (67-64-1)	
LC50 - Fish [1]	4.74 – 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: EPA)
LC50 - Fish [2]	6210 – 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: IUCLID)
EC50 - Crustacea [1]	10294 – 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 - Crustacea [2]	12600 – 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
Formic acid (64-18-6)	
LC50 - Fish [1]	130 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	120 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Crustacea [2]	138 – 165.6 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 72h - Algae [1]	26.9 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [1]	25 mg/l (Species: Desmodesmus subspicatus)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
LOEC (chronic)	> 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Blaster Rust Neutralizer

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

12.2. Persistence and degradability

Blaster Rust Neutralizer

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

Blaster Rust Neutralizer

Bioaccumulative potential	Not established.
---------------------------	------------------

2-butoxyethanol (111-76-2)

Partition coefficient n-octanol/water	0.81 (at 25 °C (at pH 7)
---------------------------------------	--------------------------

Acetone (67-64-1)

BCF - Fish [1]	(0.69 dimensionless)
----------------	----------------------

Partition coefficient n-octanol/water	-0.24
---------------------------------------	-------

Formic acid (64-18-6)

BCF - Fish [1]	(0.22 dimensionless)
----------------	----------------------

Partition coefficient n-octanol/water	-1.9 (at 23 °C (at pH 5)
---------------------------------------	--------------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified.
Other information	: No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. The generation of waste should be avoided or minimised wherever possible. Container under pressure. Do not drill or burn even after use.
Additional information	: Flammable vapours may accumulate in the container. Hazardous waste due to potential risk of explosion.

SECTION 14: Transport information

In accordance with TDG

14.1. UN number

UN-No. (TDG)	: UN1950
--------------	----------

14.2. UN proper shipping name

Proper Shipping Name (TDG)	: AEROSOLS
----------------------------	------------

Blaster Rust Neutralizer

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

14.3. Transport hazard class(es)

TDG

Transport hazard class(es) (TDG) : 2.1

Hazard labels (TDG) : 2.1



14.4. Packing group

Packing group (TDG) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

TDG

UN-No. (TDG) : UN1950

TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Parts 1 and 2, do not apply to the offering for transport, handling or transport of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.
(2) Subsection (1) does not apply to self-defence spray.

Explosive Limit and Limited Quantity Index : 1 L

Excepted quantities (TDG) : E0

Passenger Carrying Road Vehicle or Passenger : 75 L

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 126

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

Blaster Rust Neutralizer

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 16: Other information

Issue date : 07-26-2024
Revision date : 07-26-2024

Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



Safety Data Sheet (SDS), Canada - Nexreg 2022

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.