



Garage Door Spray Lubricant

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Issue date: 03/25/2021

Revision date: 03/25/2021

Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
Product name : Garage Door Spray Lubricant
Product code : 16-GDL-CND

1.2. Recommended use and restrictions on use

Recommended use : Multi-Purpose Lubricant

1.3. Supplier

Manufacturer

The Blaster Corporation
8500 Sweet Valley Drive
44125 Valley View, Ohio - USA
T (216) 901-5800 - F (216) 901-5801
www.blastercorp.com

1.4. Emergency telephone number

Emergency number : Chemtrec (800) 424-9300 customer # 2847

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Flam. Aerosol 2 H223
Press. Gas (Diss.) H280
Asp. Tox. 1 H304

2.2. GHS Label elements, including precautionary statements

This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

GHS-CA labelling

Hazard pictograms (GHS-CA) :



Signal word (GHS CA) : Danger

Hazard statements (GHS-CA) : H223 - Flammable aerosol.
H280 - Contains gas under pressure; may explode if heated.
H304 - May be fatal if swallowed and enters airways.

Precautionary statements (GHS-CA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P331 - Do NOT induce vomiting.
P405 - Store locked up.
P403 - Store in a well-ventilated place.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Garage Door Spray Lubricant

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

3.2. Mixtures

Name	Product identifier	%	Classification according to HPR
Petroleum distillates, hydrotreated light	(CAS-No.) 64742-47-8	30 – 60	Flam. Liq. 3;H226 Asp. Tox. 1;H304
Naphtha (petroleum), heavy alkylate	(CAS-No.) 64741-65-7	15 – 40	Flam. Liq. 3;H226 Asp. Tox. 1;H304
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	(CAS-No.) 68649-42-3	1 – 5	Skin Irrit. 2;H315 Eye Irrit. 2A;H319
Carbon dioxide	(CAS-No.) 124-38-9	1 – 5	Press. Gas (Comp.);H280 Simple Asphy;SIAS

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. IF SWALLOWED: Immediately call a POISON CENTER/doctor.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : May cause irritation to the respiratory tract.
- Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
- Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia.

4.3. Immediate medical attention and special treatment, if necessary

- Other medical advice or treatment : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

- Suitable extinguishing media : Dry chemical. Carbon dioxide. Halons. Foam.

5.2. Unsuitable extinguishing media

- Unsuitable extinguishing media : Do not use water jet.

5.3. Specific hazards arising from the hazardous product

- Fire hazard : Flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. hydrocarbons.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.4. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : DO NOT fight fire when fire reaches explosives. Evacuate area.
- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapours may be heavier than air and may travel along the ground to a distant ignition source and flash back. Cool closed containers exposed to fire with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate every possible source of ignition. Use only non-sparking tools. Use special care to avoid static electric charges.

6.2. Methods and materials for containment and cleaning up

- For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

Garage Door Spray Lubricant

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Do not spray on an open flame or other ignition source.
- Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.
- Additional hazards when processed : Do not pierce or burn, even after use. Hazardous waste due to potential risk of explosion.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep out of the reach of children. Store locked up. Store in a cool, well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Carbon dioxide (124-38-9)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA [ppm]	5000 ppm
ACGIH OEL STEL [ppm]	30000 ppm

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Gas
- Appearance : Aerosol
- Colour : Clear
- Odour : Mild aliphatic
- Odour threshold : No data available
- pH : No data available
- Relative evaporation rate (butylacetate=1) : No data available
- Relative evaporation rate (ether=1) : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : 360 °F (182.2 °C)
- Flash point : 130 °F (54.4 °C) (TCC)
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Flammability (solid, gas) : Flammable aerosol.

Garage Door Spray Lubricant

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Relative density	: 0.81
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available

9.2. Other information

Flame projection length	: 0 cm
Flashback	: No
Heat of combustion	: 46.6 kJ/g

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: No dangerous reactions known under normal conditions of use.
Chemical stability	: Stable under normal conditions. Flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Heat. Sources of ignition. Incompatible materials. Excessive water.
Incompatible materials	: Strong oxidizing agents. Strong reducing agents.
Hazardous decomposition products	: May include, and are not limited to: oxides of carbon. Hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

Petroleum distillates, hydrotreated light (64742-47-8)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h

Naphtha (petroleum), heavy alkylate (64741-65-7)

LD50 oral rat	> 7000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.04 mg/l/4h

Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Not classified.
Respiratory or skin sensitization	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified.

Petroleum distillates, hydrotreated light (64742-47-8)

NOAEL (animal/male, F0/P)	≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male
---------------------------	---

STOT-single exposure	: Not classified.
STOT-repeated exposure	: Not classified.

Petroleum distillates, hydrotreated light (64742-47-8)

NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Animal sex: female
NOAEC (inhalation, rat, vapour, 90 days)	≥ 0.024 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Aspiration hazard	: May be fatal if swallowed and enters airways.
-------------------	---

Garage Door Spray Lubricant

Vaporizer	Aerosol
-----------	---------

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.

Garage Door Spray Lubricant

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
-------------------	---

Petroleum distillates, hydrotreated light (64742-47-8)

LC50 - Fish [1]	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 - Fish [2]	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

Naphtha (petroleum), heavy alkylate (64741-65-7)

EC50 - Crustacea [1]	2 mg/l (Exposure time: 48 h - Species: Mysidopsis bahia)
EC50 72h - Algae [1]	30000 mg/l (Species: Pseudokirchneriella subcapitata)

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)

LC50 - Fish [1]	1 – 5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
LC50 - Fish [2]	10 – 35 mg/l (Exposure time: 96 h - Species: Pimephales promelas [semi-static])
EC50 - Crustacea [1]	1 – 1.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

Garage Door Spray Lubricant

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

Garage Door Spray Lubricant

Bioaccumulative potential	Not established.
---------------------------	------------------

Petroleum distillates, hydrotreated light (64742-47-8)

BCF - Fish [1]	61 – 159
----------------	----------

Carbon dioxide (124-38-9)

BCF - Fish [1]	(no bioaccumulation)
----------------	----------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified.
Other information	: No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. The generation of waste should be avoided or minimized wherever possible. Container under pressure. Do not drill or burn even after use.
Additional information	: Handle empty containers with care because residual vapours are flammable.

SECTION 14: Transport information


14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

UN-No. (TDG)	: UN1950
TDG Primary Hazard Classes	: 2.1 - Class 2.1 - Flammable Gas
Transport document description (TDG)	: UN1950 AEROSOLS, 2.1 (Limited quantity)
Proper Shipping Name (TDG)	: AEROSOLS (LIMITED QUANTITY)

Hazard labels (TDG)



Garage Door Spray Lubricant

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

14.2. Transport information/DOT

No additional information available

14.3. Air and sea transport

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

SECTION 16: Other information

Issue date	: 03/25/2021
Revision date	: 03/25/2021
Other information	: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.